

HÖRMANN

transDEK
...modular loading solutions



SCISSOR LIFTS

Heavy-duty scissor lifts for use in the loading bay, factory or warehouse

A surface mounted solution, suitable for internal or external locations.



A COMPACT, SURFACE MOUNTED SOLUTION IDEAL FOR SPACE RESTRICTED SITES ▲

Our range of scissor lifts provide a rugged, safe, reliable, cost-effective solution for your material handling needs, whether you are lifting goods between split levels or loading/unloading goods vehicles.

The units are surface-mounted to enable speedy install in less than 1 day, without the need for pits and civils.

CE-plated and built in conformity with EN1570 and the Machinery Directive, our scissor lifts are built for a lifetime of robust operation.



A FAST AND EFFICIENT WAY TO LOAD/UNLOAD TRAILERS ▲

Robust and built for a lifetime of operation, our scissor lifts service the loading/unloading of vehicles with trailer bed heights of up to 1590mm.

Two different lift sizes are available; 6 and 9 cage variants which offer lifting capacities of up to 3000kg UDL (raise) and 5000kg UDL (lower). The compact footprint of the lifts also means that they can be located internally or externally and/or at sites which are restricted on space.

SPECIFICATION ▲

6 and 9 roll cage models

Lifting capacities of up to 3000kg UDL (raise) and 5000kg UDL (lower)

Service range: 1590mm

Quick install - 1 day

No pits - surface mounted

Ideal for space restricted loading/unloading areas



SERVICING RAISED DOCKS ▲

For lifting goods between split levels in the warehouse or at level access sites, our scissor lifts provide an ideal solution.

The lifts are delivered as plug-and-play, modular units that are fitted straight in less than 1 day – an instant solution for your loading and lifting requirements.

OUR SCISSOR LIFT RANGE ▲

6 Cage ▲

External Pod Dimensions	2050mm (w) x 3150mm (l) x 2215mm (h)
Platform Footprint	1820mm (w) x 2830mm (l)
Load Capacity	6 roll cages
Lifting Capacity	3000kg UDL raise and lower
Closed Height	160mm
Stroke	1430mm

9 Cage ▲

External Pod Dimensions	32952mm (w) x 5280mm (l) x 2215mm (h)
Platform Footprint	2650mm(w) x 3280mm (l)
Load Capacity	9 roll cages
Lifting Capacity	2500kg UDL raise, 5000kg UDL lower
Closed Height	160mm
Stroke	1430mm



UNRIVALLED SAFETY ▲

Designed with safety in mind, the lifts encompass a range of comprehensive safety features and are built in conformance with BS/EN standards and are CE Marked.



▲ **Maintenance Safety Props**
Easily activated for safe servicing



▲ **LED Traffic Lights**
Interlocked to control panel



▲ **Sliding Personnel Gate**
Safer alternative to 'drop down' designs



▲ **Material Gates**
Fall protection gates with robust locking mechanisms



▲ **Hydraulic Lead-On Ramp**
Fixed, low gradient for easy access from ground level



▲ **Platform Safety Edge**
Enhancing safety for operators and minimising damage



▲ **Controls**
Lift can be operated from platform or ground level



▲ **Safety Curtain**
Prevents access under platform when lift is raised



Scan QR code to watch scissor lift video



Transdek UK Ltd
Bryans Close, Harworth,
Doncaster, DN11 8RY.
United Kingdom

t: +44 (0) 1302 752 276
e: info@transdek.com
i: www.transdek.com

